

Features


- Provides over-pressure protection for intermodal tank containers
- Scored, forward-acting, non-fragmenting design
- Fits standard tank car safety vents or mount between ASME B16.5 Class 150 and ISO standard flanges
- Operating pressures to 90% of the disk's marked burst pressure
- Total performance tolerance $\pm 5\%$
- See table below showing disk sizes with pressure ratings and burst temperatures ready for immediate shipment
- Materials of construction
 - Disk: Nickel
 - Positioning collar, bottom ring: 316
 - Lining: PFA
 - Gaskets: PTFE
 - Other Materials available



Standard Ratings and Temperatures

Disk Size		Pressure Rating		Burst Temperature	
in.	mm	psig	bar	°F	°C
2.50	65	54.4	3.751	68	20
2.50	65	63.8	4.399	68	20
2.50	65	54.4	3.751	140	60
2.50	65	63.8	4.399	140	60
3.00	80	54.4	3.751	140	60
3.00	80	63.8	4.399	140	60

ICP Standard Disk Construction



ICP Disk Dimensions

Disk Size		Standard Dimensions – inches (mm)					
		A		B		H	
in.	mm	in.	mm	in.	mm	in.	mm
2.50	65	3.75	95	2.50	64	0.25	6.4
3.00	80	5.00	127	2.90	74	0.38	9.7



ICP_052023

zookdisk.com



SERVING AMERICA, CENTRAL & SOUTH AMERICA
 16809 Park Circle Drive
 Chagrin Falls, Ohio 44022
 United States
 Toll Free: +1 800 543 1043
 Phone: +1 440 543 1010
 E-mail: sales@zookdisk.com

SERVING EUROPE, MIDDLE EAST & AFRICA
 Navigation House, Bridge St.
 Killamarsh, Sheffield, S21 1AL
 United Kingdom
 Phone: +44 (0) 1909 560999
 E-mail: sales.europe@zookdisk.com

SERVING CANADA
 4400 South Service Road
 Burlington, Ontario, L7L 5R8
 Canada
 Toll Free: +1 800 370 6057
 Phone: +1 905 681 2885
 E-mail: sales.canada@zookdisk.com

SERVING ASIA PACIFIC
 Menara LGB TTDI
 Unit 6-3A, Level 6, Menara LGB,
 No. 1, Jalan Wan Kadir,
 Taman Tun Dr. Ismail,
 60000 Kuala Lumpur, Malaysia
 Phone: +603 2706 0098
 E-mail: sales.asia@zookdisk.com